

## TRL Krosaki refractories limited

**TRL CRVV** 

## (Formerly Tata Refractories Limited) **Product Definition Sheet**

Revision No.: 03				Dat	te: 14.12.2019
Product Name:	TRL CRVV				
Product Description:	Direct Bonded Mag-Chrome Brick based on high purity dead burnt magnesia and Chrome Ore. Different furnaces in Non-ferrous industries and back up lining of ladle in Steel industry				
Application:					
CONTROL PROPERTIES:	·				
Chemical Analysis	ysis Unit by wt Value		Test Method		
(Calcined Basis)		Typical	Limit		
MgO	%	61.2	≥ 58.0	By XRF	
Cr <sub>2</sub> O <sub>3</sub>	%	20.4	≥ 18.0		
SiO <sub>2</sub>	%	1.4	≤ 1.7		
Fe <sub>2</sub> O <sub>3</sub>	%	8.4			
Al <sub>2</sub> O <sub>3</sub>	%	6.1			
CaO	%	0.9			
Physical Properties	Unit				
Bulk Density	gm/cc	3.12	$\geq$ 3.00	ISO 5017: 1998	
App. porosity	Vol.%	16.2	≤ 18.0	ISO 5017: 1998	
CCS	kg/cm <sup>2</sup>	520	$\geq$ 400	ISO 10059-2:2003	
RUL (t <sub>a</sub> ) at 2 kg/cm <sup>2</sup>	0C	1700		IS 1528- Part 2	
SUPPLEMENTARY PROPE	RTIES (FOR INF	ORMATION ONLY	):	-	
Property	Unit	Typical	Limit	Test Method	
PLC at 1500ºC/2hrs	%	+ 0.11		ISO 2478:1987	
Thermal Expansion at 1000ºC	%	+ 0.84		IS 1528 (Part 19): 1991	
Control Dimensions:	AQL 6.5% for	critical dimensions	(ISO 5022)		
Shelf Life	12 months from the date of manufacture when stored under shed and free from moistur				
Technology Manager					Signature:
Contact Address	TRL Krosaki Refractories Limited				
		P.O Belpahar, Dist Jharsuguda, Odisha, Pin- 768 218, INDIA			
		Phone: 91-6645-250286			
	Information department: Technology Division				

## Note:

1) The typical technical data shown are based on average results on production samples and are subjected to normal variation on individual tests. Hence, it cannot be taken as specification.

2) The above specification is valid for solid pressed standard items only. For shaped items and weight more than 20Kg may have a variation of 10%.

## **Disposal Consideration:**

May be disposed in an approved landfill unless contaminated in service. If contaminated with hazardous materials, place waste in suitable container. Seal and properly label the waste container. Send the container to an approved Transportation, Storage and Disposal (TDS) facility via an approved waste hauler. Be sure manifests have been completed and an adequate "Paper trial" has been established.